

MINI-QUENCHER

In-line Spark Arrestor, for 2 to 4 Inch Ducts

Sparks Entering



No Sparks Leaving



IMPROVED design; shorter body with more extinguishing energy

STOCK Models: (shipped in 24-36 hours, APO)

Q-2; 2"od connection, 100-150 SCFM, 4" diameter tube, 23" long*, terra brown painted steel, 10 lbs

Q-4; 4"od connection, 300-500 SCFM, 6" diameter tube, 40" long*, terra brown painted steel, 25 lbs

* Add 3" slip connections at each end

QAM reserves the right to change pricing and specifications, at any time, without notice.

TERMS: net 30 days. (OAC), see complete terms and conditions at www.qamanage.com.

FREIGHT: FOB Waterloo, ON. Shipped prepaid and charge QAM choice of carrier) or on client's freight account.

WARRANTY: Limited one year against workmanship.

DESCRIPTION:

- **A static device, with no moving parts.**
- The "Cell" consists of overlapping turbulence deflectors in a round housing, thereby creating maximum agitation and turbulence of the air stream.
- MINI-QUENCHER is designed and built specifically for spark arresting and cooling.
- **Duct Connections:** Standard is Sleeve joint / slip on.
- **Robust and abrasion resistant;** Made of 14 gauge HRS tube and internal components.

